






www.ppse.com.my  
(603) 8964 5228

# MASTERLINK & CONNECTING LINK





## G80 ALLOY MASTERLINK

CODE	WLL (Ton)	A (mm)	B (mm)	D (mm)	S (mm)	H (mm)	WT (kgs)
13B6	2.4	115	60	13	7	50	0.35
16B7	2.8	190	100	16	9	70	0.86
20B7	5.8	170	90	20	11	70	1.25
22B7	6.4	210	110	22	12	70	1.83
25B6	10.0	190	100	25	13	80	2.21
28B7	10.5	270	140	28	15	70	3.81
32B6	15.2	270	140	32	17	70	5.05
38B7	10.5	270	140	38	20	55	7.3
45B7	24.5	470	250	45	24	60	17.06



## G80 ALLOY MASTERLINK ASSEMBLY

CODE	WLL (Ton)	A (mm)	B (mm)	D (mm)	a (mm)	b (mm)	d (mm)	WT (kgs)
M16	3.8	120	70	16	95	51	13	1.19
M20	5.8	170	90	20	120	70	16	2.41
M22	7.6	170	90	22	150	80	20	3.77
M25	10.0	190	100	25	150	80	20	4.45
M28	12.7	210	110	28	170	90	22	6.12
M32	15.2	270	140	32	190	100	25	9.47
M38	25	270	140	38	270	140	32	17.4
M45	34	320	170	45	270	140	38	26.76



## G80 ALLOY CONNECTING LINK (HAMMERLOK)

CHAIN DIA. (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	P x L (mm)	WLL (TON)	WT (kgs)
6	18	45	18	7.8	7.6	14	4.8 x 38.5	1.12	0.07
7/8	23	62	25	11.5	10	18	6.3 x 53	2	0.25
10	27	72	30	12.6	12.6	23	8 x 63.5	3.15	0.35
13	34	88	36	19	16.7	27	10 x 79	5.3	0.68
16	39	103	40	21	21	33	14 x 106	8	1.10
20	47	116	48	23	23	44	14 x 108	12.5	1.70
22	55	133	51	26.5	26.5	49	16 x 134	15	2.20



For OSHA, ASME B30.9 and Manufacturer's Guidelines. Can fall if damaged, misused or overload. Inspect before use. Use only if trained. Do not exceed rated capacity. Protect from contact with edges. DEATH or INJURY can occur from improper use or maintenance.