

# 一次性使用吊装带

They are made in several width and strength according to the intended use. The slings are designed for one load only (to enable that load to be dispatched and received) and are not intended for repeated use. This type of sling would not need to be subjected to Periodic examination by a competent person, due to its disposable nature.

Safety Factor: 4:1 5:1 7:1

Standard: DIN 60005-2006 EN1492-1

Length: As required

Color: White or others

一次性吊装带可以根据现场使用制作的不同吨位、宽度。

其仅为完成一次性吊装（即，装货吊装→卸货吊装）而设计的一种经济型吊装带，而不是用于反复吊装为目的的。由于一次性吊装带本身特性，可以免于专业人员周期性的对吊装带的检查，使用方便。

安全系数：4:1 5:1 7:1

执行标准：DIN 60005-2006 EN1492-1

长度：按照客户要求

颜色：白色或其它色



## SPECIFIC:

Stock No	S.F.	WLL(kg)	Width (mm)	Stock No	S.F.	WLL(kg)	Width (mm)
OS4030	4:1	300	25	OS7060	7:1	600	30
OS4050	4:1	500	25	OS7060	7:1	600	35
OS4150	4:1	1500	35	OS7060	7:1	600	50
OS5035	5:1	350	25	OS7065	7:1	650	35
OS5038	5:1	380	25	OS7070	7:1	700	35
OS5050	5:1	500	25	OS7075-1	7:1	750	25
OS5060	5:1	600	25	OS7075-2	7:1	750	35
OS5065	5:1	650	25	OS7050-3	7:1	750	50
OS5075	5:1	750	25	OS7090	7:1	900	30
OS7030	7:1	300	25	OS7090	7:1	900	40
OS7035	7:1	350	25	OS7095	7:1	950	40
OS7040	7:1	400	25	OS7100	7:1	1000	30
OS7050-1	7:1	500	25	OS7100	7:1	1000	45
OS7050-2	7:1	500	35	OS7100	7:1	1000	50
OS7050-3	7:1	500	50	OS7200	7:1	2000	60

**WARNING:** They are not suitable for repeated use due to their comparatively light construction and low abrasive resistance. These slings should be disposed of once they have been detached from the load at the final destination.

警告：一次性吊装带不适合反复使用，因为他们比较薄、耐磨性稍差。

一次性吊装带一般仅用于将货物吊装到目的地，完成货物转移，如将货物装上船舶、随货物一起到达目的地。